



US006640846B2

(12) **United States Patent**
Strnad et al.

(10) **Patent No.:** **US 6,640,846 B2**
(45) **Date of Patent:** **Nov. 4, 2003**

(54) **AUTOMATIC FUELING SYSTEM AND
COMPONENTS THEREFOR**

(75) Inventors: **Rudolph A. Strnad**, Indian Wells, CA
(US); **Spencer P. Magleby**, Provo, UT
(US); **John F. Marshall**, Provo, UT
(US); **W. Douglas Stout**, Provo, UT
(US); **Carl D. Sorensen**, Provo, UT
(US); **Ryan W. Warnick**, Beaverton,
OR (US); **Lee Baroldy**, Provo, UT
(US); **Lisa Cloward**, Ann Arbor, MI
(US); **David S. Bent**, Mukileto, WA
(US); **Adam Gaglione**, Provo, UT
(US); **Robert Cvetko**, Simi Valley, CA
(US); **Aaron T. Schellenberg**, Canton,
MI (US)

(73) Assignee: **R. Strnad Enterprises, LLC**, Indian
Wells, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/097,149**

(22) Filed: **Mar. 12, 2002**

(65) **Prior Publication Data**

US 2002/0096226 A1 Jul. 25, 2002

Related U.S. Application Data

(62) Division of application No. 09/481,088, filed on Jan. 11,
2000, now Pat. No. 6,354,343, which is a division of
application No. 09/025,684, filed on Feb. 18, 1998, now Pat.
No. 6,024,137.

(51) **Int. Cl.⁷** **B65B 1/30**

(52) **U.S. Cl.** **141/94; 141/83; 141/98**

(58) **Field of Search** 141/94, 83, 98,
141/198, 231, 232, 284, 250, 351, 352,
387, 388; 137/234.6, 615; 901/6, 16, 46,
47; 342/42, 140; 354/295

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,642,036 A	2/1972	Ginsburgh et al.	141/94
4,665,955 A	5/1987	Horvath et al.	141/1
H297 H	7/1987	Schultz	141/232
4,681,144 A	7/1987	Horvath et al.	141/1
4,728,955 A	3/1988	Hane	342/140
4,862,856 A	9/1989	Yokoe et al.	123/519
4,881,581 A	11/1989	Hollerback	141/113
4,978,986 A	12/1990	Hatch	354/295
5,163,473 A	11/1992	Strnad, Jr.	137/588
5,383,500 A	1/1995	Dwars et al.	141/98
5,603,349 A	2/1997	Harris	137/588
5,609,190 A	3/1997	Anderson et al.	141/59
5,628,351 A	5/1997	Ramsey, Jr. et al.	141/98

(List continued on next page.)

Primary Examiner—Timothy L. Maust

(74) *Attorney, Agent, or Firm*—Fulbright & Jaworski L.L.P.

(57) **ABSTRACT**

An automatic fueling system includes a pump having a telescoping arm capable of placement in three-dimensional space, a flexibly mounted nozzle on the end of the arm and a docking cone to mate with the fuel port on a vehicle. A camera provides a view of the side of the vehicle on a monitor with guides visible to the operator of the vehicle to assist in locating the vehicle within range of the pump. A light and a camera located adjacent to the nozzle are used to recognize retro-reflective light from an annular target about the intake port. Multiple approximations of the distance and location of the intake port are made with the nozzle moving closer to mating with the intake port. A data link is provided through the mated nozzle with a keypad accessible by the vehicle operator. The vehicle includes a control actuator which selectively couples actuator cables associated with the fuel door and the fuel inlet valve with the emergency brake cable to engage the emergency brake, open the fuel door and open the inlet valve. A vacuum system on an evaporation canister insures that vapor is drawn from the fuel tank as it is being displaced by incoming fuel.

7 Claims, 8 Drawing Sheets

